

AV Distributors

The VA-13 series, newly designed as composite video/stereo distribution amplifier, can expand the RCA output socket of user's AV equipment(satellite receiver, VCR, LD and etc...) to distribute more(TV, CVR, AMP, video sender , modulator ...) and built-in clamp circuit is designed to eliminate up-down.

Features

- In/Out: Baseband (composite) Video and Left and Right Audio
- Drives up to 12~4 Audio/Video Components from a A/V Source.
- 9.5~17" Component, Space Saving inline Power Adapter
- Low A/V Distortion for Crisp Sound and Picture.
- Adjustable Video and Audio Levels



Specifications		VA-13CX	VA-13BS	VA-13AX	OM-VA13A
VIDEO	Bandwidth	20Hz~8MHz			
	Gain	6dB			
	Input Port	1 x Composite Video via RCA Connectors			
	Input Level	4Vp-p Max. (1KΩ Load)			
	Output Port	12 x Composite Video	8 x Composite Video	4 x Composite Video	4 x Composite Video
	Output Level Adj.	1.8Vp-p (75Ω Load)			
AUDIO	Bandwidth	20Hz~20KHz			
	Gain	11dB			
	Input Port	1 x Stereo Audio (R/L) via RCA Connectors			
	Input Level	5Vp-p Max. (20KΩ Load)			
	Output Port	12 x Stereo (R/L)	8 x Stereo (R/L)	4 x Stereo (R/L)	4 x Stereo (R/L)
	Output Level Adj.	4.5Vp-p (4.7KΩ Load)			
Power Consumption		5W Maximum	5W Maximum	5W Maximum	5W Maximum
Dimension (LxDxH)mm		420 x 240 x 60	345 x 203 x 60	420 x 240 x 60	240 x 150 x 50

